## **VAUTID 143**

## Wear plates for highly wear resistant hardfacing and medium impact

## VAUTID

VAUTID Material characteristics	Abrasion   Abrasion   Impact   Impact
Base materials	All weldable steels, mostly structural steels
Manufal August	Link shreeting (bigh so that allow as increased and so head and ND so thid as

Material type Alloy components	High-chromium/high-carbon alloy on iron base with embedded NB carbides $\mathbf{C}-\mathbf{Cr}-\mathbf{Nb}-\mathbf{Fe}$
Recommended applications	Similar to VAUTID 100 but with higher resistance against abrasion and impact, average resistance against corrosion and temperatures up to 350 $^\circ$ C
Weld deposit properties	Hardness (acc. DIN 32525-4): approx. 750 HV10, approx. 62 HRC*
Main industries	Mining, glass industry, metallurgical plant, cement works, power stations, etc.
Typical machine parts	Chutes, sieves, transfer stations, bunkers, mill linings, dust and ash ducts, etc.
Handling	<ul> <li>Conventional machining possible only by grinding</li> <li>Thermal cutting using laser, plasma or water jet cutting</li> <li>Cold working from diameter 300 mm possible with hard facing inside (1)</li> <li>Cold working from diameter 450 mm possible with hard facing outside (1)</li> <li>Fixing by welding or bolting on the base material</li> <li>Constructions comparable with conventional steel construction</li> </ul>

(1) dependent on thickness of plates

\* subject to common industrial fluctuations

Forms of delivery:			
Formats (mm)	Thickness of the plates Base material + Hardfacing (mm)	Material Layers	Comments
Standard formats 2.400 x 1.150 <sup>(2)</sup> 2.900 x 1.400 <sup>(2)</sup>	5+3 <sup>(3)</sup> , 6+4, 6+6, 8+5, 8+6, 8+8, 10+5, 10+10 Futher combinations on demand	≤ 6 mm: 1 Layer > 6 mm: 2 - 4 Layers	Base material 5 mm: Hardfacing 3 mm Base material 6 mm: Hardfacing3 - 6 mm Base material ≥ 8 mm: Hardfacing 3 - 20 mm
Special body Up to 3.900 x 1.900 <sup>(2)</sup>	On demand	≤ 6 mm: 1 Layer > 6 mm: 2 - 4 Layers	Base material 6 mm: Hardfacing 4 -6 mm Base material ≥ 8 mm: Hardfacing 4 -20 mm
			(2) Hardfaced area

This data sheet corresponds to the present state of production (October 2016) and can be changed anytime.

(2) Hardfaced area (3) max. 2.900 x 1.400 mm

VAUTID GROUP	Phone:	+ 49 711 / 44 04-0	E-Mail
Brunnwiesenstr. 5	Fax:	+ 49 711 / 44 20 39	Web:
73760 Ostfildern			

E-Mail: vautid@vautid.de Web: www.vautid.com