

ULTIMATE PRODUCTION

The Model 4680XP can process trees and logs nearly four feet in diameter. It can take extremely large volumes of brush and logging slash, and problematic chunk wood is easily devoured. The wide throat opening on the 4680XP also means it can out-perform every other horizontal grinder on the market, creating up to 800 yards of mulch per hour.

PRODUCE MORE, PAY LESS

The Beast's patented cuttermill utilizes a unique cutterbody holder that regulates the size of the cut. The result is a more uniform product using less energy to process material. This results in savings in fuel, wear and tear, and most importantly - time - because you get the right size on the first pass.

Standard & Custom Colors Available

Choose from two standard colors, or select a custom color to match your fleet.





The Model 4680XP is built to stand up to any daily grind. Solid steel welded construction and the industry's best components combine to create a machine professionals can trust to perform. And when you need parts or service, turn to our worldwide network of authorized dealers who are ready to offer their support.



6750 Millbrook Rd. • Remus, MI 49340 • 1-800-952-0178







Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers The Beast® Horizontal Grinders • Track Carriers • Attachments

SPECIFICATIONS

MEASUREMENTS		4680XP TRACK
Length:	41'	1,249.7 cm
Width:	11'8"	355.6 cm
Height:	12' 8"	366.08 cm
Weight:	95,200 lbs. (43,182 kg)	
Engines:	875-1,200 HP (652.5-894.8 kW)	
Fuel Tank:	400 gal. (1,514.2 L)	
Hydraulic Tank:	200 gal. (757.1 L)	

UNDERCARRIAGE AND TRACK OPTIONS

Track: 325EL Steel tracks equipped with Caterpillar track under carriage, and triple grouser shoes. 3.3 MPH (5.3km/h), 14.5" (36.83 cm)

DIMENSIONS				
Capacity:	45" Capacity	114 cm Capacity		
Opening:	45" tall x 60" wide	114 cm x 152 cm wide		
Cuttermill:	59.5" dia. x 63" wide	151 cm dia. x 160 cm wide		
Teeth:	48			
Feed Wheel:	(1) 30" dia. x 60" wide	(1) 76.2 cm x 152 cm wide		
Infeed Conveyor: Adjustable speed 10' - 60'/min. (305-1,829 cm/min.), 16'3" long x 60" wide (495.3 cm long x 152 cm wide)				
Discharge Conveyor: Primary and Secondary discharge conveyors. Secondary Conveyor: 25'6" long x 56" wide (up to 313-634 FPM conveyor speed, stacking height 18' (548.64 cm)				

ENGINE OPTION 1	ENGINE OPTION 2
Make and Model: CAT C27	Make and Model: CAT C27
Gross HP: 875 HP (652.5 kW)	Gross HP: 1050 HP (783 kW)
Fan: Reversing	Fan: Reversing
Clutch Type: HPTO15 PT Tech fluid	Clutch Type: HPTO15 PT Tech fluid

ENGINE OPTION 3

Make and Model: CAT C32

Gross HP: 1200 HP (894.8 kW)

Fan: Reversing

Clutch Type: HPT015 PT Tech fluid

COMMITTED TO QUALITY & PRODUCTIVITY

Since 1983, Bandit has manufactured equipment for a multitude of wood waste processing markets. The vision since the beginning, is to build quality, highly productive, easy to maintain equipment providing years of dependable service.

The commitment for quality, innovation and dedication is instilled in every employee and is one of the main reasons why Bandit became an Employee-Owned Company (ESOP) in 2018. These core values ensure each Bandit machine will leave the factory ready to exceed your expectations.

GO-ANYWHERE TRACK MOBILITY

Caterpillar 325EL steel track undercarriage can be added to the 4680XP. This feature allows it to travel over rough terrain not accessible by towable units. It also eliminates the need to forward or skid material to the grinder – the operator can take the grinder to the trees.



TEST OUR METAI

When you choose a Bandit whole tree chipper, you'll experience more uniform chip production, smoother and more efficient chipping, long-lasting components and improved fuel economy. We invite you to see for yourself by scheduling a demo with your nearest authorized Bandit dealer.



Bandit Offers a Complete Line of Tree Care Equipment: Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers The Beast® Horizontal Grinders • Track Carriers • Attachments